130 Adjustable Cross

Key clamp fitting for tubular handrails, barriers and frames

Tube sizes
34mm · 42mm · 48mm

An adjustable cross, often used on stair rails of 30° to 45°.



Dimension drawing to follow.
Sizes, weights and part numbers are in the table below.

SIZES AND DATA

		34mm B34	42mm C42	48mm D48
Part number		**130-B34**	**130-C42**	**130-D48**
Fits tube	outside diameter, mm (nominal bore)	33.7 (1")	42.4 (1 1/4")	48.3 (1 1/2")
FIXING AND WEIGHT				
Grub screw	BSP thread × length, mm	1/4" × 12.5	3/8" × 12.7	3/8" × 12.7
Hex key	across flats	1/4" AF	5/16" AF	5/16" AF
Weight	kg, approximate	0.63	1.03	1.15
OTHER MAKERS' PART NUMBERS for comparison				
Interclamp		130-B34	130-C42	130-D48
Q Clamp		130-2	130-3	130-4
Tubeclamp		130B	130C	130D
FastClamp		C28G25	C28G32	C28G40
Alvin		A23 size 6	A23 size 7	A23 size 8
ORDERING				
Barcode	GTIN	5061091710426	5061091710433	5061091710440

Material: Malleable cast iron (ASTM A197) **Finish:** Hot-dip galvanised

Sizes and weights are nominal figures from the foundry's data. These are galvanised castings, so individual fittings vary and it is normal for one to measure or weigh a little differently. Check the fittings in your hand before cutting tube or drilling fixing holes. Not for use as building or construction scaffolding. The strength of a structure depends on the fittings, tube and fixings chosen and on what it is fixed to. Choosing the right size and type of fitting for the job is the customer's responsibility. If in doubt, ask us.