
155 Long Tee - Ramp

Key clamp fitting for tubular handrails, barriers and frames

Tube sizes
34mm · 42mm · 48mm

A long tee for ramps, which can also join horizontal tubes. Ramp fittings are designed for ramps and other shallow gradients between 4° and 10°.





One drawing serves every size. Letters match the table below.

SIZES AND DATA

		34mm B34	42mm C42	48mm D48
Part number		**155-B34**	**155-C42**	**155-D48**
Fits tube	outside diameter, mm (nominal bore)	33.7 (1")	42.4 (1 1/4")	48.3 (1 1/2")
DIMENSIONS	nominal, mm, as lettered on the drawing			
A	barrel axis to the end of the post socket	46	60	68
B	overall length of the barrel	104	145	168
DE	bore (inside diameter of the socket, the tube passes in here)	35	44	50
DF	outside diameter of the cast body	46	55	60.5
G	barrel end face to the nearer grub-screw axis	12	15	16.5
FIXING AND WEIGHT				
Grub screw	BSP thread × length, mm	1/4" × 12.5	3/8" × 12.7	3/8" × 12.7
Hex key	across flats	1/4" AF	5/16" AF	5/16" AF
Weight	kg, approximate	0.52	0.89	1.11
OTHER MAKERS' PART NUMBERS	for comparison			
Kee Klamp		88-6	88-7	88-8
Interclamp		155-B34	155-C42	155-D48
Q Clamp		204-2	204-3	204-4
Tubeclamp		204B	204C	204D
FastClamp		C52G25	C52G32	C52G40
Alvin		G04 size 6	G04 size 7	G04 size 8
ORDERING				
Barcode	GTIN	5061091711188	5061091711195	5061091711201

Material: Malleable cast iron (ASTM A197) **Finish:** Hot-dip galvanised

Sizes and weights are nominal figures from the foundry's data. These are galvanised castings, so individual fittings vary and it is normal for one to measure or weigh a little differently. Check the fittings in your hand before cutting tube or drilling fixing holes. Not for use as building or construction scaffolding. The strength of a structure depends on the fittings, tube and fixings chosen and on what it is fixed to. Choosing the right size and type of fitting for the job is the customer's responsibility. If in doubt, ask us.