247 Kick Plate Base Flange

Key clamp fitting for tubular handrails, barriers and frames

Tube sizes
42mm · 48mm

A base flange with a kick plate fixing. The built-in mounting slots save extra drilling when fitting kickboard along an edge.



Dimension drawing to follow.
Sizes, weights and part numbers are in the table below.

SIZES AND DATA

		42mm C42	48mm D48
Part number		**247-C42**	**247-D48**
Fits tube	outside diameter, mm (nominal bore)	42.4 (1 1/4")	48.3 (1 1/2")
FIXING AND WEIGHT			
Grub screw	BSP thread × length, mm	3/8" × 12.7	3/8" × 12.7
Hex key	across flats	5/16" AF	5/16" AF
Weight	kg, approximate	2.04	2.14
OTHER MAKERS' PART NUMBERS for comparison			
Interclamp		242-C42	242-D48
Q Clamp		247-3	247-4
Tubeclamp		247C	247D
FastClamp		C18G32	C18G40
Alvin		A11 size 7	A11 size 8
ORDERING			
Barcode	GTIN	nan	nan

Material: Malleable cast iron (ASTM A197) **Finish:** Hot-dip galvanised

Fit base plates with the fixing holes in line with the load on the rail. Sizes and weights are nominal figures from the foundry's data. These are galvanised castings, so individual fittings vary and it is normal for one to measure or weigh a little differently. Check the fittings in your hand before cutting tube or drilling fixing holes. Not for use as building or construction scaffolding. The strength of a structure depends on the fittings, tube and fixings chosen and on what it is fixed to. Choosing the right size and type of fitting for the job is the customer's responsibility. If in doubt, ask us.